

## **ODS-AGM8E** (PC310)

### Technical Data Sheet

### **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

### **Power & Performance**

Voltage	12V	
Capacity (20-hour rate)	8Ah	
Capacity (10-hour rate)	7Ah	
Cold Cranking Amps (CCA, SAE J537)	100A	
PHCA - 5-second pulse current	310A	
HCA	200A	
MCA	155A	
Reserve capacity	9 mins	
Short circuit current (using IEC method)	455A	
Internal resistance at 20°C (using IEC method)	$27.1~\text{m}\Omega$	

### **Dimensions & Weight**

Length	137 mm
Width	86 mm
Height (to top of terminals)	99 mm
Height Container	99 mm
Weight	2.7 kg

### **Temperature**

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

### Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

### Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 04/07/2021 20:51:58 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366Bernville Road Reading, PA 19605, USA Tel: +1-610-208-1991 / +1-800-538-3627

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780

## Extreme AGM<sup>2</sup> ODS-AGM8E CCA- 100- ABEREVE CAUGHT - SIMILARE

# Terminal Type M4 Female Thread Thread M5 Female Thread